
FreeBSD

Korea FreeBSD Users Group – <http://www.kr.FreeBSD.org/>

Chapter 9 :

<rick@rickinc.com> .

<nobreak@kr.FreeBSD.org> .

: 2004 8 7

: 2005 3 8

: 1.0

FreeBSD Documentation Project FreeBSD Handbook 2004 8

7 . FreeBSD Handbook ,
, CVS Repository
,
,
가
가 . KFUG(Korea FreeBSD Users Group)
KFUG

“FreeBSD Handbook” “FreeBSD Documentation Project” , “ FreeBSD
” “ (Young-oak Lee)” .

Copyright © 1995, 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004 The FreeBSD Documentation Project.

9

9.1

FreeBSD

FreeBSD ; FreeBSD

FreeBSD MacOS 가
. FreeBSD

" "

:

- FreeBSD 가
- 가 가
- 가
- 가
- 가
- 가
- 가
- 가
- 가
- 가

:

- 가(8)

9.2

FreeBSD

LPD

FreeBSD

LPD

LPD

LPD

가

LPD

:

-
- 가 ;
- 가
- (*burst*)
-
- LPD
-
-

(/etc/printcap)

가

LPD

9.2.1

가

가

- LPD ; 가 가
가 .
- LPD / 가 가
(TeX DVI)
- 가

9.3

LPD

LPD

가

:

- LPD 가
- , , , ,

9.3.1

가 : LPD

- 가
- LPD (/etc/printcap)

(9.4.3.2)

" " LPD
가


9.3.1.1

PC
FreeBSD 가

가

[]

1.	가	가	PC
:			
•			
			가



[9-1.bmp]

-

PC 가

가

"Centronics"



[9-2.bmp]

- Universal Serial Bus

USB

RS232

. USB RS232

USB

가



[9-3.bmp]

()

(EPP ECP)

FreeBSD

USB

IEEE1284

가

FreeBSD

가

가

가

가


가

(

)

2.

Centronics



[9-5.bmp]

“ ”

- "DTE - DCE"
- (Short)) (hood) ("DTE - DTE")
-

DIP

가 bps (bit
(baud)) . 7 8 ; none, even, odd parity; 1 2

```
stop . ; none XON/XOFF( "in-band" "
```

9.3.1.2

FreeBSD LPD

```
가 ;
;
가
/etc/printcap LPD
```

[]

```
가
:
# grep sioN /var/run/dmesg.boot
```

```
N 0 . 가
```

```
sio2 at port 0x3e8-0x3ef irq 5 on isa
sio2: type 16550A
```

```
:
```

```
# grep ppcN /var/run/dmesg.boot
```

```
N 0 .
```

```
ppc0: <Parallel port> at port 0x378-0x37f irq 7 on isa0
ppc0: SMC-like chipset (ECP/EPP/PS2/NIBBLE) in COMPATIBLE mode
ppc0: FIFO with 16/16/8 bytes threshold
```

```
가
```

```
가
```

```
가
```

[]

9.3.1.3 /dev 가

Note: FreeBSD 5.0

devfs

가 . *devfs* 가 FreeBSD

가 . /dev

[: /dev 가,]

```

1. /dev 가

su(1) root 가 . 가 root .

/dev :

# cd /dev

:

# ./MAKEDEV port

port . lpt0

ttyd0 ttyd1 . lpt1 ; 가

:

# ls -l port

가

2. FreeBSD 가 interrupt-driven polled
   FreeBSD 4.X 5.X
   ppc(4) ppcbus(4)

● interrupt-driven GENERIC
   가 가 IRQ

● polled 가 가
    
```

가

interrupt-driven IRQ

HP 가(

) . polled 가 . 가

lptcontrol(8) 가

:

ppc0 .

ppc1 . ppc2 .

- interrupt-driven FreeBSD 4.X irq :

device ppc0 at isa? irq N

N IRQ .

FreeBSD 5.X :

hint.ppc.0 irq="N"

/boot/device.hints IRQ N .

ppc(4) 가 :

device ppc

- polled irq 가 :

FreeBSD 4.X :

```

device ppc0 at isa?

FreeBSD 5.X                               /boot/device.hints
:

hint.ppc.0.irq="N"

FreeBSD 5.X    polled
               acpi(4)

acpi(4)

lptcontrol(8) :

:

# lptcontrol -i -d /dev/lptN

lptN    interrupt-driven

:

# lptcontrol -p -d /dev/lptN

lptN    polled-

가      /etc/rc.local

lptcontrol(8)

```



```
●   가                                lptest(1)
   :

   # lptest > /dev/lptN

   N  0                                .

●   가                                :

   # cat > /dev/lptN

   RETURN    ENTER

CONTROL+D                                .

                                           :

   # cat file > /dev/lptN

   file                                가                                .

가                                .   가                                ;

5.

FreeBSD 가

                                           :

su(1)   root 가

/etc/remote                                가   :
```

printer:dv=/dev/port:br# bps -rate:pa=parity

port (*ttyd0, ttyd1*) , *bps -rate*
parity (*even, odd, none*
zero)

19200bps

가 :

printer:dv=/dev/ttyd2:br#19200:pa=none

tip(1) :

tip printer

가 /etc/remote /dev/ttydN
/dev/cuaaN .

- 가 lptest(1)

:

% \$lptest

- 가

CONTROL + D

:

% >*file*

file 가 . tip(1)

가 ;

[]

9.3.1.4 : /etc/printcap

가 ()
LPD 가 .

/etc/printcap LPD . LPD 가

printcap(5) . /etc/printcap
/usr/share/misc/termcap /etc/remote
cgetent(3) .

:

() /etc/printcap
;

sh () ;

sd ;

/dev /p /etc/printcap
가
ms#

;


```
#
# /etc/printcap for host rose
#
rattan|line|diablo|lp|Diablo 630 Line Printer:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:

                rattan    line, diablo, lp    Diablo 630 Line Printer
가          .    lp          가          가          .
                bamboo    ps, PS, S, panasonic    Panasonic KX-P4455 PostScript
v51.4          가          .

2.
LPD
가
가          sh          /etc/printcap          가          sh가
가 /etc/printcap          가          :

#
# /etc/printcap for host rose - no header pages anywhere
#
rattan|line|diablo|lp|Diablo 630 Line Printer:
        :sh:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
        :sh:

가          :
        TAB          .
```

3.

```

/var/spool
mkdir(1)

:

# mkdir /var/spool/printer-name

가 LPD rattan bamboo

:

# mkdir /var/spool/lpd
# mkdir /var/spool/lpd/rattan
# mkdir /var/spool/lpd/bamboo

Note: 가

:

# chown daemon:daemon /var/spool/lpd/rattan
# chown daemon:daemon /var/spool/lpd/bamboo
# chmod 770 /var/spool/lpd/rattan
# chmod 770 /var/spool/lpd/bamboo

/etc/printcap LPD .sd

:

#
# /etc/printcap for host rose - added spooling directories
#

```

rattan|line|diablo|lp|Diablo 630 Line Printer:

:sh:sd=/var/spool/lpd/rattan:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:

:sh:sd=/var/spool/lpd/bamboo:

sd /var/spool/lpd

4.

/dev 가 FreeBSD 가 /dev
LPD
가 (가)

/etc/printcap /dev lp

rattan *bamboo*
가 ; /etc/printcap 가 :

#

/etc/printcap for host rose - identified what devices to use

#

rattan|line|diablo|lp|Diablo 630 Line Printer:

:sh:sd=/var/spool/lpd/rattan:

:lp=/dev/lpt0:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:

:sh:sd=/var/spool/lpd/bamboo:

:lp=/dev/ttyd5:

/etc/printcap lp LPD /dev/lp

```

        . /dev/lp          FreeBSD          .
        가
        .
        .
5.
        LPD
bps ,
        :
        • /etc/printcap ;
        • 가 가
        /etc/printcap lp :
br#bps - rate
        50, 75, 110, 134, 150, 200, 300, 600, 1200, 1800,
2400, 4800, 9600, 19200, 38400, 57600 115200 bps-
rate
ms#stty - mode
        . stty(1)
LPD 가 lp ms#
        . stty(1) parenb, parodd, cs5, cs6,
cs7, cs8, cstopb, crtscts ixon
        가 bps 38400
    
```

```
-parenb      , cs8  8-bit      , clocal      crtscts
```

```
:
```

```
bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
```

```
:sh:sd=/var/spool/lpd/bamboo:
```

```
:lp=/dev/ttyd5:ms# -parenb cs8 clocal crtscts:
```

6.

LPD

(input)

LPD 가

LPD 가

lp

/bin/cat

. FreeBSD

()

lpf

가

. lpf

가 /usr/local/libexec/if-simple

```
:
```

```
#!/bin/sh
```

```
#
```

```
# if-simple - Simple text input filter for lpd
```

```
# Installed in /usr/local/libexec/if-simple
```

```
#
```

```
# Simply copies stdin to stdout. Ignores all filter arguments.
```

```
/bin/cat && exit 0
```

```
exit 2
```

```
:
```

```
# chmod 555 /usr/local/libexec/if - simple
```

```

/etc/printcap   if                               LPD 가
가 가          가   /etc/printcap              :
```

```
#
```

```
# /etc/printcap for host rose - added text filter
```

```
#
```

```
rattan|line|diablo|lp|Diablo 630 Line Printer:
```

```
    :sh:sd=/var/spool/lpd/rattan:   :lp=/dev/lpt0:
```

```
    :if=/usr/local/libexec/if - simple:
```

```
bamboo|ps|PS|S|panasonic|Panasonic KX - P4455 PostScript v51.4:
```

```
    :sh:sd=/var/spool/lpd/bamboo:
```

```
    :lp=/dev/ttyd5:ms# - parenb cs8 clocal crtscts:
```

```
    :if=/usr/local/libexec/if - simple:
```

7. LPD

```
lpd(8)  /etc/rc          lpd_enable          .          NO
          /etc/rc.conf   가          :
```

```
lpd_enable="YES"
```

```
lpd(8) .
```

```
# lpd
```

8.

```
LPD
```

```
가 . LPD
```

```
lpr(1) .
```

```
lpr(1) lptest(1)
```

```

LPD
:

# lptest 20 5 | lpr -Pprinter -name

printer-name /etc/printcap ( ).
-P lpr(1) .
lpctest(1) . lpr file
.
. lptest(1)
:

!#$%&'()*+,-./01234
"#$%&'()*+,-./012345
#$%&'()*+,-./0123456
$%&'()*+,-./01234567
%&'()*+,-./012345678

(
lpctest(1) . lptest 80 60 60 80
.

가

```

9.4

9.4.1

LPD 가

) (

quirks

가

FreeBSD
/usr/libexec/lpr/lpf () 가 FreeBSD 가

- 가 LPD 가

- LPD 가 (가

- 가

- typesetting 가
가 troff lpr -t TeX DVI lpr -d

`lpr -v`

- `lpd`는 LPD 프로세스를 실행합니다.
- `lpd`는 `lpd.conf` 파일을 사용하여 LPD 프로세스를 실행합니다. (FreeBSD 4.10 이상부터는 `lpd.conf`가 기본입니다.)

9.4.1.1 `lpd`가 `lpd.conf`가

LPD가

LPD

(`/etc/printcap` `/dev/console` `if`).

LPD가 `/etc/printcap`

`lpd(1)`가 `lpd.conf`가 `lpd -t` LPD
`lpd`가

LPD `if` (`if` : `if`)

`/etc/printcap` 3가 :

- LPD가 LPD가

filter-name [-c] -wwidth -llength -iindent -n login -h host acct-file

-c

lpr -l

width

/etc/printcap 132 pw ()

length

66 pl ()

indent

0 lpr -i () ..

login

host

LPD

exit 2

가 LPD 가 . LPD .

FreeBSD /usr/libexec/lpr/lpf (feed)
width length .

LPD . 가 exit

9.4.1.2

()

, 가 .

가 . %! () . 가

. 가

가 ?

가 가 lprps . lprps

가 (가 가

) . (lprps) textps 가 psif

```

        .
        lprps
        .

lprps FreeBSD ( ).
        . lprps lprps psif
        . lprps /etc/printcap
        :

:if=/usr/local/libexec/psif:

        LPD 가 - rw
        ( lprps 가 )
가 :

```

```

#!/bin/sh
#
# psif - Print PostScript or plain text on a PostScript printer
# Script version; NOT the version that comes with lprps
# Installed in /usr/local/libexec/psif
#

IFS="" read -r first_line
first_two_chars=`expr "$first_line" : ' (.. )'`

if [ "$first_two_chars" = "%!" ]; then
    #
    # PostScript job, print it.
    #
    echo "$first_line" && cat && printf " 004" && exit 0
    exit 2
else
    #
    # Plain text, convert it, then print it.
    #
    ( echo "$first_line"; cat ) | /usr/local/bin/textps && printf " 004" && exit 0
    exit 2

```

```
fi
```

```

        textps      가
        .           -
FreeBSD          가 a2ps
        가
    
```

9.4.1.3

```

                                de facto
        Aladdin Enterprises   FreeBSD
    Ghostscript   가
        .
        FreeBSD
        가
        가
        가 :                    500
        -sDEVICE   gs(          )          (gs -h
        가                    .).
    
```

```

#!/bin/sh
#
# ifhp - Print Ghostscript-simulated PostScript on a DeskJet 500
# Installed in /usr/local/libexec/ifhp
#
# Treat LF as CR+LF:
#
    
```

```
printf " 033&k2G" || exit 2

#
# Read first two characters of the file
#
IFS="" read -r first_line
first_two_chars=`expr "$first_line" : ' (.. )'`

if [ "$first_two_chars" = "%!" ]; then
    #
    # It is PostScript; use Ghostscript to scan-convert and print it.
    #
    # Note that PostScript files are actually interpreted programs,
    # and those programs are allowed to write to stdout, which will
    # mess up the printed output. So, we redirect stdout to stderr
    # and then make descriptor 3 go to stdout, and have Ghostscript
    # write its output there. Exercise for the clever reader:
    # capture the stderr output from Ghostscript and mail it back to
    # the user originating the print job.
    #
    exec 3>&1 1>&2
    /usr/local/bin/gs -dSAFER -dNOPAUSE -q -sDEVICE=djet500
        -sOutputFile=/dev/fd/3 - && exit 0
else
    #
    # Plain text or HP/PCL, so just print it directly; print a form feed
    # at the end to eject the last page.
    #
    echo "$first_line" && cat && printf " 033&I0H" &&
exit 0
fi

exit 2
```

if LPD :

:if=/usr/local/libexec/lfhp:

lpr plain.text lpr whatever.ps

9.4.1.4

(ASCII

)

[]

```

1. 가?
    TeX typesetting
    가 가 TeX DVI
    DVI
    :
% dvips seaweed -analysis.dvi
% lpr seaweed -analysis.ps
DVI LPD DVI
:
% lpr -d seaweed -analysis.dvi
-d DVI LPD 가
가 /etc/printcap
가
2. 가?
    
```

	/etc/printcap	lpr
cifplot	<i>cf</i>	<i>-c</i>
DVI	<i>df</i>	<i>-d</i>
plot	<i>gf</i>	<i>-g</i>
ditroff	<i>nf</i>	<i>-n</i>
FORTRAN text	<i>rf</i>	<i>-f</i>
troff	<i>rf</i>	<i>-f</i>
raster	<i>vf</i>	<i>-v</i>
plain text	<i>if</i>	none, <i>-p</i> <i>-l</i>

가 lpr -d /etc/printcap df

FORTRAN text plot Printerleaf

(Interleaf) plot

가 . gf Printerleaf lpr -g

Printerleaf

3. FreeBSD /usr/local

/usr/local/libexec LPD 가 ;

가 .

/etc/printcap

bamboo DVI 가 .

```

bamboo          df          /etc/printcap          .

#
# /etc/printcap for host rose - added df filter for bamboo
#
rattan|line|diablo|lp|Diablo 630 Line Printer:
    :sh:sd=/var/spool/lpd/rattan:
    :lp=/dev/lpt0:
    :if=/usr/local/libexec/if-simple:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
    :sh:sd=/var/spool/lpd/bamboo:
    :lp=/dev/ttyd5:ms#-parenb cs8 clocal crtscts:rw:
    :if=/usr/local/libexec/psif:
    :df=/usr/local/libexec/psdf:

DVI          /usr/local/libexec/psdf          .          가          :

#!/bin/sh
#
# psdf - DVI to PostScript printer filter
# Installed in /usr/local/libexec/psdf
#
# Invoked by lpd when user runs lpr -d
#
exec /usr/local/bin/dvips -f | /usr/local/libexec/lprps "$@"

          dvips          (-f          )          .          LPD
          lprps (
          )          . lprps

4.
          가
          가

```

```

III - SI ( GIF )

:

#!/bin/sh
#
# hpvf - Convert GIF files into HP/PCL, then print
# Installed in /usr/local/libexec/hpvf

PATH=/usr/X11R6/bin:$PATH; export PATH
giftopnm | ppmtopgm | pgmtopbm | pbmtolj -resolution 300
    && exit 0
    || exit 2

GIF 가 anymap graymap, bitmap
/PCL .

/etc/printcap 가 :

#
# /etc/printcap for host orchid
#
teak|hp|laserjet|Hewlett Packard LaserJet 3Si:
    :lp=/dev/lpt0:sh:sd=/var/spool/lpd/teak:mx#0:
    :if=/usr/local/libexec/hpif:
    :vf=/usr/local/libexec/hpvf:

bamboo groff typesetting troff

:

#!/bin/sh
#
# pstf - Convert groff's troff data into PS, then print.
# Installed in /usr/local/libexec/pstf
#
exec grops | /usr/local/libexec/lprps "$@"

```

```

                                lprps . 가
                                :

#!/bin/sh
#
# pstf - Convert groff's troff data into PS, then print.
# Installed in /usr/local/libexec/pstf
#
exec grops

                                /etc/printcap 가 가 :

:tf=/usr/local/libexec/pstf:

                                FORTRAN blush 가 가 .
                                FORTRAN- . teak :

#!/bin/sh
#
# hprf - FORTRAN text filter for LaserJet 3si:
# Installed in /usr/local/libexec/hprf
#

printf " 033&k2G" && fpr && printf " 033&l0H" &&
exit 0
exit 2

                                teak /etc/printcap 가 :

:rf=/usr/local/libexec/hprf:

                                가 . teak DVI
가 . /etc/printcap DVI :

:df=/usr/local/libexec/hpdf:

```

```

        DVI          /PCL
FreeBSD ( ) 가 : dvi2xx
        DVI          llp,      ll
2000     dviIj2p
dviIj2p     hpdf
        .dvi          /dev/fd/0
가 . (dvi ) /dev/fd/0 ( )
dviIj20 가
가 /tmp
bin     daemon     /tmp     sticky
bit     가
가
        (/etc/printcap     sd )
        /tmp     ( )     가
가
가 :

#!/bin/sh
#
# hpdf - Print DVI data on HP/PCL printer
# Installed in /usr/local/libexec/hpdf

PATH=/usr/local/bin:$PATH; export PATH

#
# Define a function to clean up our temporary files.  These exist
# in the current directory, which will be the spooling directory
# for the printer.
#
cleanup() {
    rm -f hpdf$$dvi

```

```
}

#
# Define a function to handle fatal errors: print the given message
# and exit 2.  Exiting with 2 tells LPD to do not try to reprint the
# job.
#
fatal() {
    echo "$@" 1>&2
    cleanup
    exit 2
}

#
# If user removes the job, LPD will send SIGINT, so trap SIGINT
# (and a few other signals) to clean up after ourselves.
#
trap cleanup 1 2 15

#
# Make sure we are not colliding with any existing files.
#
cleanup

#
# Link the DVI input file to standard input (the file to print).
#
ln -s /dev/fd/0 hpdf$$dvi || fatal "Cannot symlink /dev/fd/0"

#
# Make LF = CR+LF
#
printf " 033&k2G" || fatal "Cannot initialize printer"

#
# Convert and print.  Return value from dvi2p does not seem to be
```

```
# reliable, so we ignore it.
#
dvilj2p -M1 -q -e- dfhp$$dvi

#
# Clean up and exit
#
cleanup
exit 0

5.      :
              가                      (lpr(1)
      ).      가
      .      가                      가
      .
      . file
FreeBSD          apsfiler      가
              DVI
```

9.4.1.5 (output)

LPD 가 :

- LPD
- LPD 가

- LPD

가 .
 filter-name -wwidth -llength
 width pw length pl .
 가 .
 () ;
 가 byte

LPD

escape

가 (LPD

가).

LPD

LPD ()
 LPD 2 : ASCII 001
 ASCII031. 가 2 (031, 001) *SIGSTOP*
 LPD 가 *SIGCONT*

가 가 LPD 가 LPD

가 .

가 lpf .
 가 lpf
 가 lpf .

9.4.1.6 lpf:

FreeBSD /usr/libexec/lpr/lpf (lpr -i) ,
(lpr -l), ().

lpf .
lpf .

lpf 가 /etc/printcap pw pl
가

9.4.2

가 가 가
.
burst 가
가 가
가 (가).
가 LPD 가
; (9.4.2.4).

9.4.2.1

/etc/printcap sh (" sh
") .

PCL 가 :

```
#!/bin/sh
#
# hpoj - Output filter for Hewlett Packard PCL-compatible printers
# Installed in /usr/local/libexec/hpoj

printf " 033&k2G" || exit 2
exec /usr/libexec/lpr/lpf
```

of

가 *teak* /etc/printcap 가 ;
가 :

```
#
# /etc/printcap for host orchid
#
teak|hp|laserjet|Hewlett Packard LaserJet 3Si:
    :lp=/dev/lpt0:sd=/var/spool/lpd/teak:mx#0:
    :if=/usr/local/libexec/hpif:
    :vf=/usr/local/libexec/hpvf:
    :of=/usr/local/libexec/hpoj:
```

가 *teak* 가
lpr -h ; lpr(1)


Note: LPD (feed) 가
/etc/printcap ff

9.4.2.2

LPD 가

가 (rose kelly 가

outline .):



[9-6.bmp]

LPD

(from feed)

(/etc/printcap sf (form feed)
)

LPD 가 /etc/printcap sh .
:

rose:kelly Job: outline Date: Sun Sep 17 11:07:51 1995

LPD .
/etc/printcap h/ (가) .

9.4.2.3

LPD :

?

가

가 lpr -h
" " 가
lpr -h

()
가 lpr -h LPD -h

- LPD
- LPD LPRng LPD
-

```
( ) 가 ) . (
LPD
LPD 가
가
(af ) 가
/etc/printcap
sh ( ) 가
```

9.4.2.4

LPD

LPD

가 lpr -h

) 가 3 (,

```
#!/bin/sh
#
# make-ps-header - make a PostScript header page on stdout
# Installed in /usr/local/libexec/make-ps-header
#
#
# These are PostScript units (72 to the inch).  Modify for A4 or
# whatever size paper you are using:
#
page_width=612
page_height=792
```

```
border=72

#
# Check arguments
#
if [ $# -ne 3 ]; then
    echo "Usage: `basename $0` <user> <host> <job>" 1>&2
    exit 1
fi

#
# Save these, mostly for readability in the PostScript, below.
#
user=$1
host=$2
job=$3
date=`date`

#
# Send the PostScript code to stdout.
#
exec cat <<EOF
%!PS

%
% Make sure we do not interfere with user's job that will follow
%
save

%
% Make a thick, unpleasant border around the edge of the paper.
%
$border $border moveto
$page_width $border 2 mul sub 0 rlineto
0 $page_height $border 2 mul sub rlineto
currentscreen 3 -1 roll pop 100 3 1 roll setscreen
```

```
$border 2 mul $page_width sub 0 rlineto closepath
0.8 setgray 10 setlinewidth stroke 0 setgray

%
% Display user's login name, nice and large and prominent
%
/Helvetica-Bold findfont 64 scalefont setfont
$page_width ($user) stringwidth pop sub 2 div $page_height 200 sub moveto
($user) show

%
% Now show the boring particulars
%
/Helvetica findfont 14 scalefont setfont
/y 200 def
[ (Job:) (Host:) (Date:) ] {
200 y moveto show /y y 18 sub def }
forall

/Helvetica-Bold findfont 14 scalefont setfont
/y 200 def
[ ($job) ($host) ($date) ] {
270 y moveto show /y y 18 sub def
} forall

%
% That is it
%
restore
showpage
EOF
```

DVI 가 :

```
#!/bin/sh
#
# psdf - DVI to PostScript printer filter
# Installed in /usr/local/libexec/psdf
#
# Invoked by lpd when user runs lpr -d
#

orig_args="$@"

fail() {
    echo "$@" 1>&2
    exit 2
}

while getopts "x:y:n:h:" option; do
    case $option in
        x|y) ;; # Ignore
        n)   login=$OPTARG ;;
        h)   host=$OPTARG ;;
        *)   echo "LPD started `basename $0` wrong." 1>&2
            exit 2
            ;;
    esac
done

[ "$login" ] || fail "No login name"
[ "$host" ] || fail "No host name"

( /usr/local/libexec/make-ps-header $login $host "DVI File"
  /usr/local/bin/dvips -f ) | eval /usr/local/libexec/lprps $orig_args
```

가
(
가)

가 lpr " " () 가 가 .


가 : LPD 가 . 가 lpr -h LPD 가 .

LPD . psop .

9.4.3

FreeBSD : . 가 가 :


- 가 LPD .



[9-7.bmp]

•

가



[9-8.bmp]

◆ LPD

LPD 가

◆

가

가

9.4.3.1

LPD 가(LPD)
가

가 LPD

LPD 가 () LPD
가 가

LPD 가

Tip: *text* 가 LF
CRLF hplf 가

/etc/printcap

가 :

가

lp (:lp=).

sd . LPD

rm

```

rp
.

/etc/printcap
가 .

가 .
rose bamboo rattan
orchid 가 . orchid (
/etc/printcap
teak 가 ;
rose 가 :
```

```

#
# /etc/printcap for host orchid - added (remote) printers on rose
#
#
# teak is local; it is connected directly to orchid:
#
teak|hp|laserjet|Hewlett Packard LaserJet 3Si:
    :lp=/dev/lpt0:sd=/var/spool/lpd/teak:mx#0:
    :if=/usr/local/libexec/ifhp:
    :vf=/usr/local/libexec/vfhp:
    :of=/usr/local/libexec/ofhp:

#
# rattan is connected to rose; send jobs for rattan to rose:
#
rattan|line|diablo|lp|Diablo 630 Line Printer:
    :lp=:rm=rose:rp=rattan:sd=/var/spool/lpd/rattan:

#
# bamboo is connected to rose as well:
#
bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
    :lp=:rm=rose:rp=bamboo:sd=/var/spool/lpd/bamboo:
```

```
orchid :
```

```
# mkdir -p /var/spool/lpd/rattan /var/spool/lpd/bamboo
# chmod 770 /var/spool/lpd/rattan /var/spool/lpd/bamboo
# chown daemon:daemon /var/spool/lpd/rattan /var/spool/lpd/bamboo
```

```
orchid rattan bamboo . orchid 가
orchid LPD DVI /var/spool/lpd/bamboo
```

```
% lpr -P bamboo -d sushi-review.dvi
```

```
rose 가 bamboo LPD
rose . rose DVI
(bamboo 가 ).
```

9.4.3.2 가

```
가 :
```

```
( ) (
```

```
) 가 (
```

```

.
.
/etc/printcap (
), , , , TCP/IP
.
가 ; netprint
netprint
가
( , )
(FreeBSD ).
```

```
#!/usr/bin/perl
#
# netprint - Text filter for printer attached to network
# Installed in /usr/local/libexec/netprint
#
$#ARGV eq 1 || die "Usage: $0 <printer-hostname> <port-number>";

$printer_host = $ARGV[0];
$printer_port = $ARGV[1];

require 'sys/socket.ph';

($ignore, $ignore, $protocol) = getprotobyname('tcp');
($ignore, $ignore, $ignore, $ignore, $address)
    = gethostbyname($printer_host);

$sockaddr = pack('S n a4 x8', &AF_INET, $printer_port, $address);

socket(PRINTER, &PF_INET, &SOCK_STREAM, $protocol)
    || die "Can't create TCP/IP stream socket: $!";
connect(PRINTER, $sockaddr) || die "Can't contact $printer_host: $!";
while (<STDIN>) { print PRINTER; }
exit 0;
```

```
가 가 . Diablo 750-N
scrivener . 5100
가 :
```

```
#!/bin/sh
#
# diablo-if-net - Text filter for Diablo printer `scrivener' listening
# on port 5100. Installed in /usr/local/libexec/diablo-if-net
#
exec /usr/libexec/lpr/lpf "$@" | /usr/local/libexec/netprint scrivener 5100
```

9.4.4

.LPD 가

9.4.4.1

```

LPD 가 . lpr
-#5 5 .

/etc/printcap sc 가 lpr(1) -#
가 -#
:

```

lpr: multiple copies are not allowed

```

( )
/etc/printcap sc

가 . rose /etc/printcap rattan
bamboo
sc 가 :

```

```

#
# /etc/printcap for host rose - restrict multiple copies on bamboo
#
rattan|line|diablo|lp|Diablo 630 Line Printer:
    :sh:sd=/var/spool/lpd/rattan:
    :lp=/dev/lpt0:
    :if=/usr/local/libexec/if - simple:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:

```

```

:sh:sd=/var/spool/lpd/bamboo:sc:
:lp=/dev/ttyd5:ms# - parenb cs8 clocal crtscts:rw:
:if=/usr/local/libexec/psif:
:df=/usr/local/libexec/psdf:

```

```

    orchind /etc/printcap ( teak
) sc 가 :
```

```

#
# /etc/printcap for host orchid - no multiple copies for local
# printer teak or remote printer bamboo
teak|hp|laserjet|Hewlett Packard LaserJet 3Si:
    :lp=/dev/lpt0:sd=/var/spool/lpd/teak:mx#0:sc:
    :if=/usr/local/libexec/ifhp:
    :vf=/usr/local/libexec/vfhp:
    :of=/usr/local/libexec/ofhp:

rattan|line|diablo|lp|Diablo 630 Line Printer:
    :lp=:rm=rose:rp=rattan:sd=/var/spool/lpd/rattan:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
    :lp=:rm=rose:rp=bamboo:sd=/var/spool/lpd/bamboo:sc:

```

```

sc lpr -# 가 lpr(1)
:
```

```

% lpr forsale.sign forsale.sign forsale.sign forsale.sign forsale.sign
( ) .
```

9.4.4.2

```

    /etc/printcap rg 가
rg
```

(root) 가 : “lpr: Not a member of the restricted group” 가 .

sc () (rg

rattan artists bamboo
rose /etc/printcap :

```
#
# /etc/printcap for host rose - restricted group for bamboo
#
rattan|line|diablo|lp|Diablo 630 Line Printer:
    :sh:sd=/var/spool/lpd/rattan:
    :lp=/dev/lpt0:
    :if=/usr/local/libexec/if - simple:

bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
    :sh:sd=/var/spool/lpd/bamboo:sc:rg=artists:
    :lp=/dev/ttyd5:ms# - parenb cs8 cllocal crtscts:rw:
    :if=/usr/local/libexec/psif:
    :df=/usr/local/libexec/psdf:
```

/etc/printcap (orchid) orchid
bamboo 가 .

Note:

9.4.4.3

가 가 가

```
LPD                                mx                                1024
BUFSIZ                             0                                mx
                                   1000
```

Note: 가

LPD

```

rattan bamboo 가 가
5 MB
```

```
#
# /etc/printcap for host rose
#
#
# No limit on job size:
#
rattan|line|diablo|lp|Diablo 630 Line Printer:
    :sh:mx#0:sd=/var/spool/lpd/rattan:
    :lp=/dev/lpt0:
    :if=/usr/local/libexec/if - simple:

#
# Limit of five megabytes:
#
bamboo|ps|PS|S|panasonic|Panasonic KX - P4455 PostScript v51.4:
    :sh:sd=/var/spool/lpd/bamboo:sc:rg=artists:mx#5000:
    :lp=/dev/ttyd5:ms# - parenb cs8 clocal crtscts:rw:
    :if=/usr/local/libexec/psif:
    :df=/usr/local/libexec/psdf:
```

/etc/printcap *mx*

;

9.4.4.4

LPD 가 :

```

가 LPD /etc/hosts.equiv
/etc/hosts.lpd LPD
LPD
:
/etc/hosts.equiv ruserok(3) rsh(1) rcp(1)
:
rose /etc/hosts.lpd

```

```

orchid
violet
madrigal.fishbaum.de

```

```

rose 가 orchid violet madrigal.fishbaum.de
가 rose LPD

```

가

minfree

```
가 : minfree
```

```
bamboo minfree 가
/etc/printcap ; bamboo 가 :
```

```
bamboo|ps|PS|S|panasonic|Panasonic KX-P4455 PostScript v51.4:
:sh:sd=/var/spool/lpd/bamboo:sc:rg=artists:mx#5000:
:lp=/dev/ttyd5:ms# - parenb cs8 clocal crtscts:rw:mx#5000:
:if=/usr/local/libexec/psif:
:df=/usr/local/libexec/psdf:
```

```
sd . LPD 가
3 MB (6144 ) :
```

```
# echo 6144 > /var/spool/lpd/bamboo/minfree
```

```
/etc/printcap rs 가
. rs 가 가
LPD . LPD LPD
```

```
가 /usr/bin/false
“token”
```


FreeBSD 가 "lpf:

pac(8)

LPD

./etc/printcap af

가

LPD

(pw pl) lpf . lpf

2.00 rose:andy
3.00 rose:kelly
3.00 orchid:mary
5.00 orchid:mary
2.00 orchid:zhang

lpf

lpf

/etc/printcap af=acct

acct

가 pac(8)

pac

Login	pages/feet	runs	price
orchid:kelly	5.00	1	\$ 0.10
orchid:mary	31.00	3	\$ 0.62
orchid:zhang	9.00	1	\$ 0.18
rose:andy	2.00	1	\$ 0.04
rose:kelly	177.00	104	\$ 3.54
rose:mary	87.00	32	\$ 1.74
rose:root	26.00	12	\$ 0.52

total	337.00	154	\$	6.74
-------	--------	-----	----	------

pac(8) :

-Pprinter

printer . /etc/printcap af 가

-c

-m

gamma smith . alpha smith
가 .

-pprice

/etc/printcap pc price
2 () . price

-r

-s

name...

names

pac(8)가

가 (가
pac -m :

Login	pages/feet	runs	price
andy	2.00	1	\$ 0.04
kelly	182.00	105	\$ 3.64
mary	118.00	35	\$ 2.36
root	26.00	12	\$ 0.52
zhang	9.00	1	\$ 0.18
total	337.00	154	\$ 6.74

```
pac(8) /etc/printcap ( 200 2 )
pc 가
-p pac(8) -p
가 가 1 50
```

pac -pl.50

```
pac -s
_sum 가 . pac(8)
가 .
```

9.4.5.2

가?

가 : 가

lpf (lpf:)

lpf

가?

DVI

DVI

dvilj dvips

가

가?

가

가

가

가

가

가

9.5

FreeBSD

:

lpr(1)

lpq(1)

lprm(1)

LPD

lpc(8)

lpr(1), lprm(1)

lpq(1) 3 가 /etc/printcap

/ -P printer-name

. -P PRINTER

. PRINTER

lp

PRINTER

PRINTER

가

lp

9.5.1

% lpr filename ...

lpr(1)

가

% lpr /etc/host.conf /etc/hosts.equiv

% lpr -P printer-name filename ...

rattan

% ls -l | lpr -P rattan

lpr(1)

lpr ls -l

lpr(1)

9.5.2

lpr(1)

LPD

가

lpq(1)

-P

bamboo

% lpq -P bamboo

lpq

```
bamboo is ready and printing
```

Rank	Owner	Job	Files	Total Size
active	kelly	9	/etc/host.conf, /etc/hosts.equiv	88 bytes
2nd	kelly	10	(standard input)	1635 bytes
3rd	mary	11	...	78519 bytes

```

bamboo          3          .          kelly 가
9 가          .          가
가
.
9          ;          lpr(1)
.          ( active "Rank" )
가          .          lpr(1)
.          mary 가 ;
가          lpq(1)          3          (.)
.
lpq(1)          :          가          (
가          LPD 가          )
lpq(1)          -/          .          lpq -l
가 :

```

```
waiting for bamboo to become ready (offline ?)
```

kelly: 1st	[job 009rose]
/etc/host.conf	73 bytes
/etc/hosts.equiv	15 bytes
kelly: 2nd	[job 010rose]
(standard input)	1635 bytes
mary: 3rd	[job 011rose]
/home/orchid/mary/research/venus/alpha-regio/mapping	78519 bytes

-P

rattan

% lprm -P rattan -

Note:

lprm(1)

```
% lpr -P rattan myfile
% rlogin orchid
% lpq -P rattan
Rank  Owner      Job  Files          Total Size
active seeyan   12   ...          49123 bytes
2nd   kelly      13   myfile         12 bytes
% lprm -P rattan 13
rose: Permission denied
% logout
% lprm -P rattan 13
dfA013rose dequeued
cfA013rose dequeued
```

9.5.4

lpr(1)

9.5.4.1

lpr(1)
pr(1)

가

bamboo : DVI (TeX typesetting) fish-report.dvi

% lpr -P bamboo -d fish-report.dvi

DVI ditroff

Note: -p -T

가 . -d DVI 가 .

-c

cifplot .

-d

DVI .

-f

FORTTRAN .

-g

plot .

-i number

number ; *number*

8

Note: *-i*

-i

-n

ditroff(troff)

-P

pr(1)

pr(1)

-T title

pr(1)

title

-p

가

-t

troff

-v

raster

가 : ls(1)
:

```
% zcat /usr/share/man/man1/lpr.1.gz | troff -t -man | lpr -t
```

```
zcat(1)      ls(1)      GNU troff
             lpr (      LPD      )
troff(1)     .      -t      lpr(1)     GNU troff
             가      .
```

9.5.4.2

lpr(1) LPD 가 :

- # *copies*

가

```
parser.c  parser.h      3      :
```

```
% lpr -#3 parser.c parser.h
```

- m

LPD 가

가

- s

가)
. LPD 가

: LPD 가

Note: LPD

-s

-r

-s

!

9.5.4.3

lpr(1)

가

-C *text*

text

-J *text*

text

stdin .

-h

Note:

9.5.5

. lpc(8)

. lpc(8)

:

- /
- /
-

: 가

가 가

(root)

가

lpc(8)

root

lpc(8)

lpc(8)

name

. *printer-name* *all*

/etc/printcap

printer-

abort *printer-name*

가

clean *printer-name*

. 가

LPD

disable *printer-name*

가

(root)

: root

가

enable

down *printer-name message*

disable

stop

. *message*

lpq(1) lpc status

enable *printer-name*

가

help *command-name*

command-name . *command-name*

restart *printer-name*

. LPD 가
stop down
restart abort start .

start *printer-name*

stop *printer-name*

가

topq *printer-name job-or-username*

printer-name *job* *username*
. *printer-name* *all* .

up *printer-name*

; down . start enable .

lpc(8)

lpc(8)

exit, quit

9.6

FreeBSD LPD
:"
가(FreeBSD 가)?"

LPRng

"LPR: " **LPRng** PLP
Patrick Piwell Justin Mason (PLP) LPRng
LPRng <http://www.lprng.org>

CUPS

Common UNIX Printing System **CUPS** 가

Easy Software Products 가

CUPS Internet Printing Protocol
(IPP) . Line Printer Daemon(LPD) Server Message Block (SMB)
AppSocket (a.k.a JetDirect) . **CUPS**

PostScript Printer Description (PPD) 가 .

CUPS <http://www.cups.org/>

9.7

lptest(1)

가 PRINT
REMAINING FORM FEED

가
FORM FEED (

)

/usr/local/libexec/if - simple

```
#!/bin/sh
#
# if - simple - Simple text input filter for lpd
# Installed in /usr/local/libexec/if - simple
#
# Simply copies stdin to stdout. Ignores all filter arguments.
# Writes a form feed character ( f) after printing job.

/bin/cat && printf " f" && exit 0
exit 2
```

" "

:

```
!"#$%&'()*+,-./01234
"$%&'()*+,-./012345
#$%&'()*+,-./0123456
```

가
 가 .
 : ASCII 10, (LF). MS-DOS, OS/2
 가 ASCII 10 ASCII 13 (carriage return
 CR). MS-DOS .

FreeBSD

가 .

FreeBSD 가 :

Printer received CR Printer prints CR
 Printer received LF Printer prints CR + LF

가 :

●

Note: FreeBSD 가
 CR LF .

●

FreeBSD 가 LF
 CR+LF . /etc/printcap ms#
onlcr .

●

escape code 가 LF
 . 가 escape .
 escape

PCL escape

가 . 가 LF LF CR ;

```
#!/bin/sh
#
# hpif - Simple text input filter for lpd for HP-PCL based printers
# Installed in /usr/local/libexec/hpif
#
# Simply copies stdin to stdout. Ignores all filter arguments.
# Tells printer to treat LF as CR+LF. Ejects the page when done.

printf " 033&k2G" && cat && printf " 033&l0H" && exit 0
exit 2
```

orchid /etc/printcap 가 . teak
3Si 가

```
#
# /etc/printcap for host orchid
#
teak|hp|laserjet|Hewlett Packard LaserJet 3Si:
    :lp=/dev/lpt0:sh:sd=/var/spool/lpd/teak:mx#0:
    :if=/usr/local/libexec/hpif:
```

가 가

. FreeBSD 가

LF 가 CR

LF CR

:

Printer receives Printer prints

CR	CR
LF	CR + LF

가 .

가 .

가 .

가 .

(가 :

).

가

- 가 XON/XOFF *ms#* *ixon*
FreeBSD .
- 가 (carrier) *ms#* *crtscs*
.

가 .

가 . *br*

bps *ms#* ; 가

/etc/printcap .

가 FreeBSD
/etc/printcap (if) 가
rattan lf 가 :

rattan|line|diablo|lp|Diablo 630 Line Printer:

:sh:sd=/var/spool/lpd/rattan:

:lp=/dev/lpt0:

:if=/usr/local/libexec/lf - simple:

:lf=/var/log/rattan.log

(
/var/log/rattan.log)

lf

LPD

/dev/console